ENGINEERING DEPARTMENT UNIVERSITY OF DELHI DELHI-110007

Ref. No. UE/

/DU/M- (2021-2022) NOTICE INVITING QUOTATION dated 0 8 2 - 21

Sealed percentage rate quotation are hereby invited from the contractor enlisted with CPWD, MES, Railways and working contractor of Delhi University for the work "Distempering and painting work in room no. 303, Department of Commerce, University of Delhi. 'So as to reach the office of the undersigned upto 3.00 P.M. on. 1

Item	0.5	100		
Applying one coat of water thinnable cement primer of approved brand and manifestory	Qty		Rate	Amount
on was surface. Water thinnable cement primer	55	sqm	60.00	3300.00
Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work		5qm	121.55	729.30
Providing and applying white cement based putty of average thickness 1 mm of approved	77			1
smooth complete. over the plastered wall surface to prepare the surface even and	55	sqm	115.15	6333.25
reas than 50 greatly here, or approved brand and manufacture, including applying additional				
coats wherever required, to achieve even shade and colour. Two coats	55	sam	106.80	5874.00
accopping, sand papering and preparing the surface smooth including necessary repairs to	55	sam	18 25	1003.75
Repairs to plaster of thickness 12 mm to 20 mm in patches of area 3.5 so motors and		1.0	200	2003.73
plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge With compet mortes 144	5	sqm	429.60	2148.00
it Petipul 4 Pharty sand)	2	anch	1000.00	
Repair work of traps for attending seepage leakage problem (4 supplies of		COCH	1099.00	3267.00
n-charge.	1	each	1985.00	1985.00
			Total	24640.30
Ris marcon				24640
ondition;			Sul	24040
	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface. Water thinnable cement primer. Painting with synthetic enamel paint of approved brand and manufacture to give an even shade. Two or more coats on new work. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface. Water thinnable cement primer Painting with synthetic enamel paint of approved brand and manufacture to give an even shade. Two or more coats on new work Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound.) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of tubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. With cement mortar 1:4 (Icement 4 charge sand) P/F CP brass jet spray (for EWC) with flexible pipe, nut bolts, screws etc all complete Repair work of traps for attending seepage leakage problem l/c cutting and making good the same leak proof the seepage point complete in all respect as per direction of Engineer-in-Charge. Fotal	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface. Water thinnable cement primer Painting with synthetic enamel paint of approved brand and manufacture to give an even shade. Two or more coats on new work. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth comolete. Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound.) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. With cement mortar 1:4 (Trement 4 marks sand) P/F CP brass jet spray (for EWC) with flexible pipe, nut bolts, screws etc all complete Repair work of traps for attending seepage leakage problem i/c cutting and making good the same leak proof the seepage point complete in all respect as per direction of Engineer-in-Charge. Total	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface. Water thinnable cement primer of approved brand and manufacture to give an even shade. Two or more coats on new work Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content iess than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scrapcing to gitting the patch in proper shape, raking out joints and preparing and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of tubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. With cement mortar 1:4 (Iroment 4 marker sand). P/F CP brass jet spray (for EWC) with flexible pipe, nut bolts, screws etc all complete Repair work of traps for attending seepage leakage problem i/c cutting and making good the same leak proof the seepage point complete in all respect as per direction of Engineer-in-Charge. Total

1 The work should be completed in 07 days.

- 1.50% water charges will be deducted.
- Rates should be quoted both in words & figures.
- The contractor must visit the site before quoting his rates.
- 5 CPWD specification in force will be followed.
 - Undersigned reserves the authority to reject any or all the quotation without assigning any reason therefore.

Executive Engineer

I/we hereby quote.....

Undertaking:

I/we hereby undertake that my/our agency have not been black listed/debarred in any Govt. organization since last 3 years.

(Contractor)

- The Director, Computer Center with a request to display the Notice inviting quotation on the Delhi University Website.
- Sh. Vijender Kumar Meena, J.E. (C.)
- Mrs. Kavita, IACT to ensure the display of the quotation notice on University website.
- Notice Board

Executive Engineer